



## Product Certification Letter

To Whom It May Concern:

This will certify that Pecora 890NST Silicone sealant conforms to the requirements of ASTM Specification C-920, Type S, Grade NS, Class 100, Use NT, T<sub>2</sub>, G, A, M and O. Conforms to the requirements of ASTM C-719. Additionally it has movement capability of 100% extension and 50% compression.

Pecora 890NST Silicone is certified for use on natural stones such as marble, granite, and limestone and has been successfully tested to ASTM C-1248 Staining of Porous Substrates by Joint Sealants.

Pecora 890NST conforms to ASTM C1382 Test Method for Determining Tensile Adhesion Properties of Sealants When Used in Exterior Insulation and Finish Systems (EIFS) Joints.

Also, this certifies that Pecora 890NST Silicone sealant conforms to requirement of Federal Specification TT-S-001543A (COM-NBS), June 9, 1971, non-sag Class A and Class B, as well conforming to Interim Federal Specification TT-S-00230C, Amendment 2, Class A and Class B, February 20, 1970, Type II non-sag.

Pecora 890NST Silicone contains 98g/l volatile organic content (VOC). Reaction product of cure not included in VOC determination.

Pecora 890NST is USDA approved and acceptable for use in processing and storage for meat and poultry processing plants.

This product is manufactured in Harleysville, Pennsylvania.

Pecora sealants and waterproofing products are manufactured in the United States and meet the requirements for use as "Domestic End Products," as stated in the Buy American Act Title 41 USC 10.

The test for an item of domestic construction material has two parts:

1. It must be manufactured in the United States, and
2. The cost of the products domestic components must exceed 50 percent of the cost of all components.

Pecora 890NST Silicone does not contain asbestos, PCB, Urea-Formaldehyde or lead as part of its formulation.

Pecora 890NST Silicone is validated through SWRI.

Sincerely yours,

A handwritten signature in black ink, appearing to read 'Roy D. Cannon, Jr.', is positioned above the printed name.

Roy D. Cannon, Jr.  
Technical Service Director  
PECORA CORPORATION





## Dynaspan Limited Material Warranty

Warranty #: XXXX

**Date:** Sample  
**Project Reference:** Sample  
**General Contractor:** Sample  
**Applicator:** Sample  
**Owner:** Sample  
**Completion Date:** Sample  
**Attention:** Sample

Pecora Corporation warrants its product to be manufactured free from defects in material and workmanship.

Under this warranty, Pecora will be responsible for the cost of replacement material for any materials made necessary by a failure of the sealant under this for a period of (# of years) of substantial completion (shown below).

**Product:** Dynaspan, Dynatred Urethane  
**Primer:** P-75

The holder of this warranty shall notify Pecora or the applicator in writing of any claims within 30 days from the discovery of any defect. Pecora will then have 30 days in which to schedule an inspection of the installation to determine if Pecora's products are not performing as intended. Pecora reserves the right to run performance tests on building material samples in its laboratory and/or field tests of actual surfaces to which Dynaspan has been applied. The owner agrees to provide the manufacturer/applicator field representatives with access to the affected areas of the project for purpose of testing and evaluating the performance of the sealant application.

This warranty becomes effective only upon full payment for all Pecora materials and labor used on the referenced project and becomes null and void if remedial repairs are performed without written authorization from either the manufacturer or the applicator.

This warranty specifically excludes failure of the sealant due to:

- a) Natural causes such as lightning, earthquake, hurricane, tornado, fire, etc.;
- b) Movement of the structure resulting in stresses on the sealant which exceed Pecora's published specification for elongation and/or compression for the sealant, whether due to structural settlement, design error or construction error;
- c) Disintegration of the underlying substrates;
- d) Mechanical damage to the sealant caused by individuals, tools or other outside agents, or
- e) Changes in the appearance of the sealant from the accumulation of dirt or other contaminants deposited on the sealant from the atmosphere.

This is Pecora's sole warranty with respect to its products. Pecora makes no other warranty of any kind, whatever, expressed or implied, and all implied warranties of merchantability and fitness for a specific purpose which exceed this obligation are hereby disclaimed by Pecora and excluded. In no case will Pecora be responsible for liquidated, incidental or consequential damages.



Any claim or controversy between or among the parties arising out of or relating to the application described herein shall be settled by arbitration in accordance with the rules of the American Arbitration Association, and judgment upon the award rendered by the arbitrator may be entered into a court having jurisdiction.

PECORA CORPORATION

---

Roy D. Cannon, Jr.  
Director of Technical Service

Sample