



Product Certification Letter

To Whom It May Concern:

This will certify that Dynaflex SC one part, non-sag, pick resistant, elastomeric, STPU hybrid joint sealant conforms to requirements of Federal Specification TT-S-00230C, Type II, Class B.

Pecora Dynaflex SC conforms to the requirements of ASTM Specification C-920, Type S, Grade NS, Class 12.5, Use T₁, M, G, A and O. Dynaflex SC has a Shore A Hardness 55 +/- 5 (ASTM C-661).

Dynaflex SC contains 15 g/l volatile organic content (VOC). This product is manufactured in Harleysville, Pennsylvania.

DynaFlex SC complies with the private office and classroom exposure scenarios of CDPH Standard Method v1.1-2010 (California Specification 01350). When tested, the range of total VOCs after 14 days (336 hours) was 0.5mg/m³ or less.

Pecora sealants and waterproofing products are manufactured in the United States and meet the requirements for use as "Domestic End Products," as stated in the Buy American Act Title 41 USC 10.

The test for an item of domestic construction material has two parts:

1. It must be manufactured in the United States, and
2. The cost of the products domestic components must exceed 50 percent of the cost of all components.

This product is chemically acceptable for use in processing or storage for meat or poultry food products by the USDA Service.

Pecora Dynaflex SC does not contain asbestos, PCB, or lead as part of its formulation.

Sincerely yours,

A handwritten signature in black ink, appearing to read 'Roy D. Cannon, Jr.', is written over a light blue horizontal line.

Roy D. Cannon, Jr.
Technical Service Director
PECORA CORPORATION