



Green Building Certification Data

MasterFormat Designation: 07 92 00 – Joint Sealants

June 27, 2017

RE: Pecora 895NST Structural Silicone Glazing & Weatherproofing Sealant

Pecora Corporation hereby declares the following information for Pecora 895NST:

LEED® v4 and LEED® 2009:

MR Credit Building Product Disclosure and Optimization–Sourcing of Raw Materials, Option 2 (*MR Credit 4.1 and 4.2, Recycled Content): For the purposes of the LEED Rating System, Pecora 895NST contains 0% recycled content.

MR Credit Building Product Disclosure and Optimization–Sourcing of Raw Materials, Options 1 and 2 (*MR Credit 5.1 and 5.2, Regional Materials): Pecora 895NST is manufactured in Harleysville, PA 19438. Due to the complexity of its raw material supply chain, the point source of Pecora 895NST's material ingredients cannot be determined.

EQ Credit Low-Emitting Materials, Options 1 and 2 (*IEQ Credit 4.1, Low-Emitting Materials–Adhesives & Sealants):

VOC Content: Pecora 895NST contains 98 g/L volatile organic compound (VOC) content, well below the 250 g/L VOC content limit for architectural sealants set by South Coast Air Quality Management District (SCAQMD) Rule 1168 (effective 7/1/2005).

VOC Emissions (LEED v4 and LEED 2009 for Schools): Pecora 895NST has been tested and meets the interior air quality (IAQ) emissions requirements for the classroom, private office, and new single-family residential scenarios of CDPH Standard Method v1.1-2010 (California Specification 01350). After 14 days (336 hours), the total VOC was <2 µg (0.002 mg)/m³, well within the lowest of three prescribed TVOC ranges.

* LEED 2009 credits and options (June 30, 2021 sunset date)

Green Globes for New Construction

Criterion 3.7.2.1 Volatile Organic Compounds: Pecora 895NST contains 98 g/L volatile organic compound (VOC) content, well below the 250 g/L VOC content limit for architectural sealants set by South Coast Air Quality Management District (SCAQMD) Rule 1168.

Living Building ChallengeSM 3.0

Imperative 08 Healthy Interior Environment: Pecora 895NST has been tested and meets the interior air quality (IAQ) emissions requirements for the classroom, private office, and new single-family residential scenarios of CDPH Standard Method v1.1-2010 (California Specification 01350). After 14 days (336 hours), the total VOC was <2 µg (0.002 mg)/m³.

Imperative 10 Red List: Contact the Technical Services Department.

Imperative 13 Living Economy Sourcing: Pecora 895NST is manufactured in Harleysville, PA 19438.

'USGBC' and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.





Should you require additional information, please contact the Technical Services Department at 1-800-523-6688 or techservices@pecora.com.

Sincerely,

A handwritten signature in black ink that reads 'Steven T. Lawrey'.

Steven T. Lawrey AIA, CSI, CCPR, CCS, CCCA, LEED® AP
Building Science Engineer
Pecora Corporation

'USGBC' and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.



STANDARD COLOR GUIDE

Custom colors available upon request.

Color Packs for Standard and Non- Standard Colors are sold in 5 unit increments.

This guide offers a representation of color; when matching is critical, a cured or applied color sample is highly recommended.

PECORA CORPORATION

165 Wambold Road
Harleysville, PA 19438

800.523.6688

pecora.com

Dynatrol™ II | Dynaflex | Dynatred™

2-PART URETHANE

BRITE WHITE	CF26	TAN	545
TRU-WHITE	345	BUFF	512
OFF-WHITE	516	COLONIAL TAN	CF13
DOVER SKY	CF14	MOCHA CREAM	CF34
ANODIZED ALUMINUM	804	TOASTED ALMOND	CF54
BRUSHED PEWTER	CF42	NATURAL STONE	565
ALUMINUM STONE	515	DESERT TAN	530
STONE GREY	CF53	ADOBE ACCENT	CF10
LONDON FOG	CF44	REDWOOD TAN	CF43
DARK GRAY	048	BRICK RED	CF16
LIMESTONE	039	TILE RED	CF22
PUTTY GREY	CF20	RED ROCK	955
PEARL ASH	CF11	RIVER ROUGE	CF37
VAN DYKE	CF18	SIERRA TAN	CF47
NATURAL WHITE	CF33	ROSE	CF05
SANDSTONE	951	TEXAS PINK	CF48
DESERT SUN	CF41	SMOKY BROWN	CF45
EGGSHELL CREAM	CF04	BRONZE	314
MANOR WHITE	CF08	CHARCOAL GRAY	950
PRECAST	113	CHOCOLATE	CF49
AMARILLO WHITE	CF02	CLASSIC BRONZE	046
ALMOND	792	GRANITE GREY	CF30
BEIGE	595	BLACK	012
PRAIRIE CLAY	CF07	PATRIOT BLUE	CF01
SANDALWOOD BEIGE	CF09	EVERGREEN	CF03
BEIGE GREY	525		

STANDARD COLOR GUIDE

Custom colors available upon request.

Minimum order quantity for non-standard colors:
200 Gallons

This guide offers a representation of color; when matching is critical, a cured or applied color sample is highly recommended.

PECORA CORPORATION

165 Wambold Road
Harleysville, PA 19438

800.523.6688

pecora.com

PECORA SECURITY SYSTEMS

Dynaflex SC

SILYL TERMINATED POLYURETHANE (STPU)

TRU-WHITE

345

LIMESTONE

039

Dynapoxy™ EP-1200

2-Part Epoxy

Dynatrol™ II

2-Part Urethane

Dynaflex

2-Part Urethane

Dynapoxy™ EP-1200, Dynatrol™ II, and Dynaflex can be used with the 51 standard colors represented on the reverse side of this card. Custom colors available upon request.

COVERAGE CHART (231 cu. in./gal.)

Joint Depth (in.) x Width (in.)	Linear Feet/ Gallon	Joint Depth (in.) x Width (in.)	Linear Feet/ Gallon	Joint Depth (in.) x Width (in.)	Linear Feet/ Gallon
1/8 x 1/8	1,232.0	1/4 x 3/4	102.7	1/2 x 7/8	44.0
1/8 x 1/4	616.0	1/4 x 7/8	88.0	1/2 x 1	38.5
1/8 x 3/8	410.7	1/4 x 1	77.0	5/8 x 5/8	49.3
1/8 x 1/2	308.0	3/8 x 3/8	136.9	5/8 x 3/4	41.1
1/8 x 5/8	246.4	3/8 x 1/2	102.7	5/8 x 7/8	35.2
1/8 x 3/4	205.3	3/8 x 5/8	82.1	5/8 x 1	30.8
1/8 x 7/8	176.0	3/8 x 3/4	68.4	3/4 x 3/4	34.2
1/8 x 1	154.0	3/8 x 7/8	58.7	3/4 x 7/8	29.3
1/4 x 1/4	308.0	3/8 x 1	51.3	3/4 x 1	25.7
1/4 x 3/8	205.0	1/2 x 1/2	77.0	7/8 x 7/8	25.1
1/4 x 1/2	154.0	1/2 x 5/8	61.6	7/8 x 1	22.0
1/4 x 5/8	123.2	1/2 x 3/4	51.3	1 x 1	19.3

Joint Depth (in.) x Width (in.) x Length (in.) x 0.053 = Gallons Required