



Product Certification Letter

To Whom It May Concern:

This will certify that Pecora Dynatrol II-SG two part, cold-applied, self-leveling, polyurethane sealant conforms to the requirements of ASTM Specification C920, Type M, Grade P, Class 25, Use T₁, M and O as well as conforms to the requirements of ASTM C719 with a movement capability of 25% extension and 25% compression.

Also, this certifies that Pecora Dynatrol II-SG sealant conforms to requirement of Federal Specification TT-S-00227E (COM-NBS) October 9, 1970, Amendment 3, Type I, self-leveling Class A on concrete when properly primed. In addition, Pecora Dynatrol II-SG sealant meets the requirements of Federal Specification SS-S-195b, February 1970, when properly primed, and Federal Specification SS-S159b, August 28, 1958, when properly primed.

Pecora Dynatrol II-SG contains <1g/L volatile organic content (VOC).

Pecora Dynatrol II-SG is USDA approved and acceptable for use in processing and storage for meat and poultry processing plants.

This product is manufactured in Harleysville, Pennsylvania.

Pecora sealants and waterproofing products are manufactured in the United States and meet the requirements for use as "Domestic End Products," as stated in the Buy American Act Title 41 USC 10.

The test for an item of domestic construction material has two parts:

1. It must be manufactured in the United States, and
2. The cost of the products domestic components must exceed 50 percent of the cost of all components.

Pecora Dynatrol II-SG does not contain asbestos, PCB, Urea-Formaldehyde or lead as part of its formulation.

Sincerely yours,

A handwritten signature in black ink, appearing to read 'Roy D. Cannon, Jr.'.

Roy D. Cannon, Jr.
Technical Service Director
PECORA CORPORATION

