



Product Certification Letter

To Whom It May Concern,

This will certify that Pecora Dynaflex two-part, non-sag, cold-applied, chemically curing elastomeric polyurethane joint sealant conforms to the requirements of Federal Specification TT-S-00227E, Type II, Class B.

Pecora's Dynaflex sealant conforms to ASTM C-920-98, Type M, Grade NS, Class 12.5. Dynaflex is tamper resistant with a Shore A Hardness of 55 +/-5 in accordance to ASTM C-661.

Pecora Dynaflex also conforms to Floor and Wall joint systems as outlined in UL Designs FF-S-0017 and WW-S-0021.

This product is chemically acceptable for use in processing or storage for meat or poultry food products by the USDA Service.

The VOC content for the Dynaflex activator is 0 g/l and the base is 80 g/l. This product is manufactured Harleysville, Pennsylvania.

Pecora sealants and waterproofing products are manufactured in the United States and meet the requirements for use as "Domestic End Products," as stated in the Buy American Act Title 41 USC 10.

The test for an item of domestic construction material has two parts:

1. It must be manufactured in the United States, and
2. The cost of the products domestic components must exceed 50 percent of the cost of all components.

Pecora's Dynaflex sealant does not contain asbestos, PCB, or lead as part of its formulation.

Sincerely yours,

Roy D. Cannon, Jr.
Technical Service Director
PECORA CORPORATION