

Product Certification Letter

To Whom It May Concern:

This will certify that Pecora 322FC two-part, self-leveling silicone pavement sealant conforms to the following specifications:

ASTM Specification C920, Specification for Elastomeric Joint Sealants, Class 100, Type M, Grade SL, Use T, M, O

ASTM C719, Specification for Adhesion and Cohesion of Elastomeric Joint Sealants under Cyclic Movement, Movement Capability (100% expansion/50% compression)

ASTM D5893, Specification for Cold Applied, Single Component, Chemically Curing Silicone Joint Sealant for Portland Cement Concrete Pavements, Type SL.

Federal Specifications TT-S-00230C and TT-S-001543.

USDA approval for use in meat and poultry processing plants.

Pecora 322FC Silicone (mixed) contains 50 g/l volatile organic content (VOC).

This product is manufactured in Harleysville, Pennsylvania.

Pecora sealants and waterproofing products are manufactured in the United States and meet the requirements for use as "Domestic End Products," as stated in the Buy American Act Title 41 USC 10.

The test for an item of domestic construction material has two parts:

1. It must be manufactured in the United States, and
2. The cost of the products domestic components must exceed 50 percent of the cost of all components.

This product is classified as non-hazardous and contains no materials or compounds listed under California Proposition 65.

Pecora 322FC Silicone does not contain asbestos, PCB, or lead as part of its formulation.



PECORA CORPORATION
Roy D. Cannon, Jr.
Technical Service Director

