

Product Certification Letter – 896

To Whom It May Concern:

This will certify that Pecora 896 Silicone sealant conforms to the requirements of ASTM Specification C920, Type S, Grade NS, Class 50, Use NT, G, A, M and O. Conforms to the requirements of ASTM C719. Additionally it has movement capability of 50% extension and 50% compression.

This will certify that Pecora 896 silicone sealant conforms to the requirements of ASTM C1184, Type S, Use G.

Pecora 896 complies with AAMA803.3 Type I & II, 805.2, Group C (Back-Bedding Glazing Compound).

Pecora 896 Silicone is certified for use on natural stones such as marble, granite, and limestone and has been successfully tested to ASTM C1248 Staining of Porous Substrates by Joint Sealants.

Also, this certifies that Pecora 896 Silicone sealant conforms to requirement of Federal Specification TT-S 001543A (COM-NBS), June 9, 1971, non-sag Class A and Class B, as well conforming to Interim Federal Specification TT-S-00230C, Amendment 2, Class A and Class B, February 20, 1970, Type II non-sag.

Pecora 896 Silicone contains <50g/l volatile organic content (VOC). This product is manufactured in Harleysville, Pennsylvania.

Material shipped into VOC regulated areas will include the designation “LV” in finished good code and will comply with VOC limits of <50g/L as designated by SCAQMD Rule 1168 effective 1/1/19.

Pecora sealants and waterproofing products are manufactured in the United States and meet the requirements for use as “Domestic End Products,” as stated in the Buy American Act Title 41 USC 10.

The test for an item of domestic construction material has two parts:

1. It must be manufactured in the United States, and
2. The cost of the products domestic components must exceed 50 percent of the cost of all components.

Pecora 896 Silicone does not contain asbestos, PCB, or lead as part of its formulation.

Sincerely,



Roy D. Cannon, Jr.
Director, Construction Materials Technology
PECORA CORPORATION

