



## **Green Building Certification Data**

MasterFormat Designations: 07 25 00 – Weather Barriers; 07 27 00 – Air Barriers; 07 27 26 – Fluid-Applied Membrane Air Barrier

November 20, 2019

RE: Pecora ProPerm VP Fluid-applied, Vapor-permeable, Water-based, Vapor-retarding Water-resistive Air Barrier

Pecora Corporation hereby declares the following information for Pecora ProPerm VP:

### LEED® v4 and LEED® 2009:

**EA Prerequisite, Minimum Energy Performance & EA Credit, Optimize Energy Performance** (\*EA Prerequisite 2, Minimum Energy Performance & EA Credit 1, Optimize Energy Performance): When installed in exterior wall assemblies in accordance with printed instructions, Pecora *ProPerm VP*, together with Pecora *XL-Flash*, *AVB Silicone Sealant*, and *XL-Span*, Pecora *ProPerm VP* may be specified to meet the continuous air barrier and joint sealing requirements contained in ASHRAE 90.1-2010 (LEED v4) and -2007 (LEED 2009) and, the 50% AEDG (Advanced Energy Design Guide Series).

MR Credit, Building Product Disclosure and Optimization—Sourcing of Raw Materials, Option 2 (\*MR Credit 4.1 and 4.2, Recycled Content): For the purposes of the LEED Rating System Pecora *ProPerm VP* contains 0% recycled content.

MR Credit, Building Product Disclosure and Optimization—Sourcing of Raw Materials, Options 1 and 2 (\*MR Credit 5.1 and 5.2, Regional Materials): Pecora *ProPerm VP* is manufactured in Harleysville, PA 19438. Due to the complexity of its raw material supply chain, the point source of Pecora *XL-Perm*'s material ingredients cannot be determined.

**EQ Prerequisite Minimum Indoor Air Quality Performance (\*IEQ Prerequisite 1, Minimum Indoor Air Quality Performance):** Together with meeting the minimum ventilation rates prescribed by Section 6 of ASHRAE 62.1-2010 (LEED v4) or -2007 (LEED 2009), installing an air barrier assembly consisting of Pecora *ProPerm VP, XL-Flash*, and, where necessary, *AVB Silicone Sealant* and/or *XL-Span*, is a design strategy that can limit the introduction of contaminants from potential outdoor sources such as heavy traffic, dense neighborhoods, and/or on-site contamination.

# EQ Credit, Low-Emitting Materials, Options 1 and 2 (\*IEQ Credit 4.1, Low-Emitting Materials—Adhesives & Sealants):

**VOC Content:** 20 g/L volatile organic compound (VOC) content; Pecora *ProPerm VP* complies with the VOC limits of the California Air Resources Board (CARB) 2007 Suggested Control Measure (SCM) for industrial maintenance coatings (maximum 250 g/L) and with the VOC limits set by South Coast Air Quality Management District (SCAQMD) Rule 1113 (effective 2/26/2016) for building envelope coatings (maximum 100 g/L).

'USGBC' and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.















**EQ Credit, Construction Indoor Air Quality Management Plan (\*IEQ Credit 3.1, Construction Indoor Air Quality Management Plan—During Construction):** Due to its water-resistive property, the newly installed and exposed Pecora *ProPerm VP* system will, in conjunction with fenestration and other water-resistive building enclosure products, protect absorptive materials that are installed and/or stored within the building envelope from moisture damage.

\* LEED 2009 prerequisites, credits, and options

#### **Green Globes for New Construction, Version 1.50**

**Criterion 3.5.10.1 Air Barriers:** Pecora *ProPerm VP* complies with the air permeability and air leakage requirements of ASTM E 2178 and ASTM E 2357, respectively.

### Living Building Challenge<sup>SM</sup> 3.1

**Imperative 10 Red List:** None of the chemicals listed on the "Living Building Challenge 3.1 Chemical Red List" are used in the manufacture of Pecora *ProPerm VP*. Based on Pecora's current knowledge of its raw materials and manufacturing processes, there is no reason to expect that the listed chemicals would be present in Pecora *Perm VP* as supplied, except as a possible trace impurity. In addition, the ingredients used in the manufacture of Pecora *Perm VP* are listed on its Globally Harmonized Safety Data Sheet (GHS SDS) together with its VOC content.

Should you require additional information, please contact the Technical Services Department at 1-800-523-6688 or <a href="techservices@pecora.com">techservices@pecora.com</a>.

Sincerely,

Steven T. Lawrey AIA, CSI, CCPR, CCS, CCCA, LEED® AP

**Building Science Engineer** 

Stem J. Saury

Pecora Corporation

'USGBC' and related logo is a trademark owned by the U.S. Green Building Council and is used by permission.









